

CENTER 200 SERIES MINI CLAMP METER



- AC/DC Current(201)
- Pocket Size
- High Speed Bargraph
- DATA HOLD Function
- Touch ZERO Function (201)
- Auto Power Off
- Autoranging
- Measuring Frequency From Current Clamp & Test Terminal



CE IEC 1010 300V CATIII
600V CATII

CENTER®

GENERAL SPECIFICATIONS


Numerical Display:

3-3/4 digital liquid crystal display(LCD),Maximum reading 3999.

Battery Life:

200hr approx. (CENTER 200) 50hr approx. (CENTER 201)

Low Battery Indication:

The  is displayed.

Sampling Rate:

Digital:2 Times/sec ; Analog Bargraph:20 Times/sec

Power Source:

1.5V, Size AAA battery × 2

Auto Power Off:

30 minute

Operating Temperature and Humidity:

0°C to 40°C (32°F to104°F) below 80%RH

Storage Temperature and Humidity:

-10°C to 60°C (14°F to140°F) below 70%RH

Dimensions: (L)× (W)× (H)

193×50×28mm ; 7.60"×1.97"×1.10"

Weight:

Approx.240g

Jaw Opening Diameter:

Cables 25mm(CENTER 200) Cables 30mm(CENTER 201)

Accessories:

Carrying case, Battery, Instruction Manual & Test Lead

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	40A	0.01A	$\pm 1.9\%rdg+5dgt(200)$
	400A	0.1A	$\pm 2.0\%rdg+5dgt(201)$
DCA	40A	0.01A	$\pm 2.5\%rdg+5dgt$
	400A	0.1A	
ACV	400V	0.1V	$\pm 1.5\%rdg+5dgt$
	600V	1V	
DCV	400V	0.1V	$\pm 1\%rdg+5dgt$
	600V	1V	
Ohm	400 Ω	0.1 Ω	$\pm 1\%rdg+2dgt$
·))	·))	Active Sound Level: $\leq 40 \Omega$	
Hz(A)	4KHz	1Hz	$\pm 0.1\%rdg+1dgt$
	10KHz	10Hz	
Hz(V)	4KHz	1Hz	$\pm 0.1\%rdg+1dgt$
	40KHz	10Hz	
	400KHz	100Hz	
	1MHz	1KHz	



ACTUAL SIZE
1 : 1

CENTER[®]

Distributed by: