

CENTER 222 MINI AC/DC CLAMP METER


FEATURE

- Pocket Size
- 4 digits Display
- Peak Hold Function
- Data Hold Function
- 0.1A Resolution at Full Range
- Touch Zero Function
- Auto Power Off

GENERAL SPECIFICATIONS

Numerical Display: 4 digital liquid crystal display

Sampling Rate: 2 Times/sec

Low Battery Indication: The  is displayed.

Battery Life: 80 hr approx.(alkaline)

Battery Type: 1.5V, Size AAA battery × 2

Auto Power Off: 30 minute

Operating Temperature: 0°C to 40°C

Storage Temperature: -10°C to 60°C

Dimensions: 187(L)×50(W)×29(H)mm

Weight: Approx.220g

Jaw Opening Diameter: Cables 25mm

Accessories:

Carrying case, Battery, Instruction Manual and Test Lead

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
DCA	600A	0.1A	$\pm 2.5\%rdg+10dgt$
ACA	600A	0.1A	$\pm 2\%rdg+5dgt$
ACV	600V	0.1V	$\pm 1.5\%rdg+5dgt$
DCV	600V	0.1V	$\pm 1\%rdg+2dgt$
Ohms	1000Ω	0.1Ω	$\pm 1\%rdg+3dgt$
·)))	·)))	Active Sound Level: $\leq 100\Omega$	

Peak Hold Capture Time: 10ms



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®
CENTER TECHNOLOGY CORP.

Distributed by: