

CENTER 202 TRUE RMS CLAMP METER

Jaw Opening Diameter: 25mm

● FEATURE

- TRUE RMS
- Autoranging
- Auto Power Off
- High Speed Bargraph
- DATA HOLD Function
- IEC 1010 600V CAT II 300V CAT III

● GENERAL SPECIFICATIONS

Display: 3-3/4 digital LCD display, 4000 count.

Low Battery Indication: The  is displayed.

Sampling Rate: Digital: 2 Times/sec ;

Analog Bargraph: 20 Times/sec

Battery : 1.5V, Size AAA battery × 2

Dimensions: 193(L) × 50(W) × 28(H)mm

Weight: Approx. 240g

Accessories: Carrying case, Battery, Instruction Manual & Test Lead

● ELECTRICAL SPECIFICATIONS

ACA (Auto Ranging)

Range	Resolution	Accuracy
40A	0.01A	±1.9%rdg+5dgts
400A	0.1A	

ACV (Auto Ranging)

Range	Resolution	Accuracy
400V	0.1V	±1.5%rdg+5dgts
600V	1V	

DCV (Auto Ranging)

Range	Resolution	Accuracy
400V	0.1V	±1%rdg+2dgts
600V	1V	

OHM

Range	Resolution	Accuracy
400Ω	0.1Ω	±1%rdg+2dgts

••••)

Range	Active Sound Level
••••)	≤40Ω

HZ Current Input (Auto Ranging)

Range	Resolution	Accuracy
20Hz-4KHz	1Hz	±0.1%rdg+1dgt
10KHz	10Hz	

HZ Voltage Input (Auto Ranging)

Range	Resolution	Accuracy
10Hz-4KHz	1Hz	±0.1%rdg+1dgt
40KHz	10Hz	
400KHz	100Hz	



*The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®

Distributed by: