



► TDS-Portable

pH/Cond/TDS/Temp Meter

Model:

PCT-401 Conductivity Meter
PCT-402 Conductivity Meter
PCT-403 pH/Cond./TDS
Meter
PCT-404 pH/Cond/Temp
Meter
PCT-405 TDS Meter



Features:

1. Rugged design for handheld or bench top use, neckstrap for "hands-free" operation.
2. Large 3-1/2 digit LCD built into adjustable "flip-up" cover.
3. Wide measuring range from 10 to 19,990 uS/cm for conductivity or 10 to 19,990 ppm for TDS. Calibrate for changes in cell constants via a cell adjust.

Specifications:

	401	402		403			404			405
	Cond.	Cond.	Temp.	pH	Cond.	TDS	pH	Cond.	Temp.	TDS
Range:	0-20K	0.1-200 uS	0-100°C	0-14.00	0-20K	0-20K	0-14.00	0-20K	0-100°C	0-20K
		1-2000 uS								
		10-20K uS								
		0.1-200mS								
Resolution:	10	0.1/1	0.1	0.01	10	10	0.01	10	0.1	10
Accuracy:	±5%	±5%	0.3	0.02	±5%	±5%	0.02	±5%	0.3	±5%
ATC	0-100°C									
Power:	9V	9V or AC Adaptor		9V						
Dimension	96x120x46mm (folded)									