



Certified by ISO 9001

ALARMAS Sonoras ///////////////

Koino®

ALARMAS SONORAS



KH-4025-1
KH-4025-2



KH-402-1
KH-402-2



KH-403-1
KH-403-2



KH-403C-1 / KH-403CD - 24
KH-403C-2 / KH-403CF - 24



KH-404-1
KH-404-2



KH-4016

MODELO	ALIMENTACION	CARACTERÍSTICAS	VOLUMEN	DIMENSIONES	
KH-4025-1	110VAC	Para montaje en Panel. Electromecánica	65dB a una distancia de 1m	Ø25, □46mm	
KH-4025-2	220VAC			Ø30, □46mm	
KH-402-1	110VAC				
KH-402-2	220VAC			Ø66, □80mm	
KH-403-1	110VAC				
KH-403-2	220VAC				
KH-403C-1	110VAC	Para montaje Superficial Electromecánica		80 x 80 x 61.5 xmm	
KH-403C-2	220VAC				
KH-404-1	110VAC				58,5 x80,5x38mm
KH-404-2	220VAC				
KH-403CD-24	24 Vdc	Electrónica: Sonido Continuo	80 x 80 x 61.5 xmm		
KH-403CF-24		Electrónica: Sonido intermitente			
KH-4016-24HD	12~24 VAC/DC	Montaje en panel. Electrónica Sonido HD: Continuo Sonido HF: Intermitente Sonido HW: Trémulo	85dB	Ø16	
KH-4016-24HF					
KH-4016-24HW					